

EN2997 connectors

upgraded performance AECMA specification vs. MIL-DTL-83723 Series III



Apollo Aerospace Components is a franchised distributor of selected mil-specification connectors for leading QPL manufacturers. We offer a comprehensive inventory of backshells, contacts and connector accessories.

Improved medium-sized environmentally resistant circular connectors based on the MIL-DTL-83723 Series III form factor, but complies with the more stringent EN2997 European standards.



Product Features

- As per MIL- DTL- 83723 Series III but additionally meets more stringent EN2997 specification for AECMA demands
- Metal to metal grounding between receptacles and plugs, improved RFI continuity
- - 65degC to +260degC cyclic operating temperature
- Ability to withstand an extended range of fluids in an aerospace environment

Product Benefits

- Designed to deliver higher performance capability for application in severe environmental applications such as aircraft engines, pressure and temperature sensors.
- Special fuel tank versions available
- Meets EN European requirements



Apollo Aerospace Components
The Clock House, Gaters Mill,
Mansbridge Road,
Southampton, SO18 3HW

T: +44 (0) 1489 861378
E: electrical-sales@apollo-aerospace.com

www.apollo-aerospace.com

EN2997 connectors

upgraded performance AECMA specification vs. MIL-DTL-83723 Series



Product technical description

General: Medium density contact arrangements with fine thread secure coupling in corrosion resistant shells.

Temperature: -65degC (-85degF) to +125degC (+500degF)

Durability: 500 mating cycles min.

Corrosion Resistance: 48 hours per EN2997

Shell to shell conductivity: max potential drop not exceeding 10mV

Contact Current Ratings: #20 5A, #16 10A, #12 17A

Technical description is typical and varies per class.

How to order

EN2997 Series (example)

EN2997	6	KE	1624	F	6
AECMA Designation	Shell Size	Class	Contact Arrangement	Contact Style	Alternative Keying
AECMA is the European Association of Aerospace Industries					

EN2997 connectors are compatible with MIL-DTL-83723 Series III contact arrangements, there are also special arrangements not shown on the table below. Please contact Apollo Aerospace Components for availability.

EN2997 ORDERING INFORMATION

Class	KE	Stainless steel, firewall (+260 degC)
	SE	Stainless steel, firewall (+260 degC) with grounding spring
	YE	Stainless steel hermetic (+260 deg C)
Shell Style	0	Square flange receptacle
	1	Solder mount receptacle (hermetic only)
	6	Plug, non-decoupling
	7	Jam nut receptacle (hermetic only)
Shell Size	8, 10, 12, 14, 16, 18, 20, 24, 28	
Contact Arrangement	See MIL-C-83723 specification or product page	
Contact Style	M	Standard pin
	A	Pin insert less contacts
	F	Standard socket
	D	Socket insert less contacts
Alternative Keying	N	Normal
	6	Variant
	7	Variant
	8	Variant
	9	Variant
	Y	Variant

These connectors are fully interchangeable and intermateable with MIL-DTL-83723 Series III threaded and Rolls Royce ESC10 connectors.

FOR REFERENCE

INSERT CONFIGURATION BY SHELL SIZE

Shell Size	NUMBER OF CONTACTS			
	Total	20	16	12
8-2	2	2		
8-3	3	3		
8-98	3	3		
10-2	2	2		
10-5	5	5		
10-6	6	6		
10-20	2		2	
12-3	3		3	
12-12	12	12		
14-4	4			4
14-7	7		7	
14-12	12	9	3	
14-15	15	15		
16-10	10		10	
16-24	24	24		
18-8	8			8
18-14	14		14	
18-31	31	31		
20-16	16		16	
20-25	25	19		6
20-28	28	24		4
20-39	39	37	2	
20-41	41	41		
22-12	12			12
22-19	19			19
22-32	32	26		6
22-39	39	27	12	
22-55	55	55		
24-19	19			19
24-43	43	23	20	
24-57	57	55		2
24-61	61	61		